
## **INTRODUCTION-Y2**

This is a 1.69-inch left-mounted color screen display with small and exquisite design, which can finely fit multiple e-bike styles.

Its ergonomic remote features a curved shape that perfectly fits the thumb arc, providing a comfortable operating experience throughout the entire ride.

## **PRODUCT ADVANTAGES**

- OCA full lamination
- IPX7 waterproof rating
- Multicolored riding mode
- Panel connectors
- Type-C charging port
- Wide voltage:10V-100V
- Compatible with UART /CAN protocol
- Soda-lime glass hardness value:6h
- Display brightness:450cd/m²



## **PRODUCT PARAMETERS**



















	Parameter	
Size	L*W*H	57.9*48.2*51.3mm
	A*B	27.7*32.6mm
	С	1.69"
	D	Ø22.2mm
Screen	Туре	TFT color matrix
	Resolution	240*280px
Connector	Connector type	Panel connectors
	Wire length(approx.)	500mm
Core data	Rated voltage	36V/48V
	Assisted mode	4 Gear modes / 9 Digital modes
	Operating temperature	-20~50°C
	Waterproof rating	IPX7
	Weight(total)	46±5g
	Compatible protocol	UART/CAN
Premium functions	Bluetooth	Supported
	Light sensor	Yes
	USB-C charging voltage	5V
	Max. USB-C charging current	500mA
Test & Certification		CE/Rohs/EN15194/Reach

Display items	Setting items
Current speed	Display Brightness
Assistance level	Automatic switch-off time
Motor output	Unit switch
E-Bike battery charge indicator	Assistance mode switch
Single journey distance	Automatic lighting
Total distance	Reset
Average speed	Wheel size
MAX speed	-
Light indicator	-
Walk assistance	-

19